

Specification:

		ROLLS	TILES	RUGS
Classification	EN 685	33	33	33
Weight	ISO 8543	2.7 – 3.1kg/m ²	3 – 3.5kg/m ²	2.2 – 2.6kg/m ²
Thickness	ISO 1765	2.5 – 2.8mm	2.5 – 2.8mm	2.5 – 2.8mm
Roll length	EN 426	20-25m	-	-
Roll width	EN 426	1.8m	-	2m
Tile Dimension	EN 994	-	50x50cm	-
Dimension stability	ISO 2551	< 0.25%	< 0.25%	< 0.25%
Curvature	EN 434	< 2mm	< 2mm	< 2mm
Caster Chair	EN 985	Continuous use	Continuous use	Continuous use
Body voltage	ISO 1815	≤ 2.0KV	≤ 2.0KV	≤ 2.0KV
Thermal resistance	ISO 8302	Suitable for underfloor heating	Suitable for underfloor heating	Suitable for underfloor heating
Color fastness to light	ISO 105-B02	> 6	> 6	> 6
Anti-slip property	EN 13893	> 0.3	> 0.3	> 0.3
Reaction to fire	EN 13501-1	Bfl-s1	Bfl-s1	Bfl-s1
Smoke density	ASTM E662	< 450	< 450	< 450
REACH test	1907/2006	NO. (6614)008-1228-R2		
CE certification	EN 14041 EN 15114	NO. EC.1282. OA 140305.AYD0738		
ISO 9001 certification	ISO 9001:2008	NO. 04514Q20096R05		
ISO 14001 certification	ISO 14001:2004	NO. 04514E20029R05		

